

FRONTIER RIG 32 | RIG INVENTORY

DRAWWORKS: 2000 HP, National 1320-UE with Baylor 7838 Auxiliary Electric Brake p/b (2) High

Torque GE 752 Electric Motors

MOBILITY: 90' Skid System

MAST: Branham 142', 1.3M lb Static Hook Load on 10 lines

SUBSTRUCTURE: 31.5' Floor Height, (3) 10' Boxes, 1' Skid Beam, .5' Rigmat

GENERATORS: (3) Caterpillar 3512C Diesel Engines w/ 1,365 KW Generators

Control House: SCR: 1600A 4x4 Bay M&I Electric with Dynamic Braking and PLC Failover System

MUD PUMPS: (2) 1600 HP FB1600 Mud Pumps with 7,500 PSI Fluid System, with P-Quip liner and

piston retention systems

TOP DRIVE: Canrig 1250AC 500 Ton Top Drive with 7,500 PSI Fluid System and Rig Floor

Mounted TDSU

CATWALK: Canrig PC-3000 Hydraulic Catwalk with Walking Package, Hydraulic V-Door,

Wireless Control

HANDLING TOOL: National ST-80C, Tall with Driller Console Safety Enable

ROTARY TABLE: National 275, 27.5" Table

BOP: 13-5/8" 5,000 PSI Double Ram with 13-5/8" 5,000 PSI Annular

MUD SYSTEM: 1,100 bbl. Mud Tanks with 48" Mud/Gas Separator, 6"x8" Mixing Pumps and 10 HP

Agitators, De-Sander, De-Silter

SHALE SHAKERS: (3) MI SWACO Linear Motion

CHOKE MANIFOLD: 4" 5,000 PSI Skid Mounted

FUEL TANK: 12,000 Gallon Dual Wall Fuel Tank w/ integrated redundant fuel pumps

WATER TANK: 500 BBL

DOG HOUSE: 10' x 8' x 45' DS, 10' x 8' x 22' ODS

TRAVELING BLOCK: 500 Ton National Traveling Block Strung on 10 Lines.

MISCELLANEOUS: Parts House, Pipe Racks, Misc. Handling Tools

LIGHTING SYSTEM: 100% LED Class I DIV I, Class I DIV II Area, Spot and Flood Fixtures

HPU: Centralized HPU with Redundant Motors/Pumps and Temp/Level Protection

4801 Richmond Sq., Oklahoma City, OK 73118 | Phone 405-745-7700 | Fax 405-745-6700